

Null MAC

Cisco AP 1

iPhone Client

AP wired B

AP wired A

qos_marking_appleiphone6_bronze_wired.pcapng

Probe Request (0x0004)

Dst	84:b2:61:24:a2:00
Src	00:00:00:00:00:00
Seq	0

Data (0x0020)

Dst	00:56:cd:ee:f1:71
Src	00:23:5d:c9:5a:c7
BSS	84:b2:61:24:a2:00
Seq	0
Len	36

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	64

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	80

Data (0x0020)

Dst	00:23:5d:c9:5a:c7
Src	00:56:cd:ee:f1:71
BSS	84:b2:61:24:a2:00
Seq	1792
Len	36

Probe Request (0x0004)

Dst	84:b2:61:24:a2:00
Src	00:00:00:00:00:00
Seq	0

Probe Request (0x0004)

Dst	84:b2:61:24:a2:00
Src	00:00:00:00:00:00
Seq	0

Probe Request (0x0004)

Dst	84:b2:61:24:a2:00
Src	00:00:00:00:00:00
Seq	0

[Frame 1] Probe Request – active scanning: client solicits responses from APs; directed (specific SSID) or wildcard (broadcast SSID); faster than passive scanning (beacon-only)

Frame 2 | 2017-01-22T23:35:52.377429Z

Frame 5 | 2017-01-22T23:35:52.451367Z

Frame 6 | 2017-01-22T23:35:52.451881Z

Frame 8 | 2017-01-22T23:35:52.490539Z

[Frame 29] Probe Request – active scanning: client solicits responses from APs; directed (specific SSID) or wildcard (broadcast SSID); faster than passive scanning (beacon-only)

[Frame 103] Probe Request – active scanning: client solicits responses from APs; directed (specific SSID) or wildcard (broadcast SSID); faster than passive scanning (beacon-only)

[Frame 113] Probe Request – active scanning: client solicits responses from APs; directed (specific SSID) or wildcard (broadcast SSID); faster than passive scanning (beacon-only)