

Cisco AP 1

Client E

AP wired B

AP wired A

Null MAC

qos_marking_bittiumsd41_alloy_wired.pcapng

Data (0x0020)

Dst	18:01:e3:04:fe:4a
Src	00:23:5d:c9:5a:c7
BSS	84:b2:61:24:a2:00
Seq	0
Len	36

Data (0x0020)

Dst	00:23:5d:c9:5a:c7
Src	18:01:e3:04:fe:4a
BSS	84:b2:61:24:a2:00
Seq	1792
Len	36

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	64

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	80

Probe Request (0x0004)

Dst	84:b2:61:24:a2:00
Src	00:00:00:00:00:00
Seq	0

Frame 1 |
2017-01-23T19:45:33.011232Z

Frame 2 |
2017-01-23T19:45:33.015471Z

Frame 12 |
2017-01-23T19:45:33.267343Z

Frame 13 |
2017-01-23T19:45:33.269307Z

💡 [Frame 57] Probe Request – active scanning: client solicits responses from APs; directed (specific SSID) or wildcard (broadcast SSID); faster than passive scanning (beacon-only)