

Cisco AP 1

Client E

Null MAC

AP wired B

AP wired A

qos_marking_bittiumsd41_silver_wired.pcapng

Data (0x0020)

Dst	18:01:e3:04:fe:4a
Src	00:23:5d:c9:5a:c7
BSS	84:b2:61:24:a2:00
Seq	0
Len	36

Data (0x0020)

Dst	00:23:5d:c9:5a:c7
Src	18:01:e3:04:fe:4a
BSS	84:b2:61:24:a2:00
Seq	2304
Len	36

Probe Request (0x0004)

Dst	84:b2:61:24:a2:00
Src	00:00:00:00:00:00
Seq	0

Probe Request (0x0004)

Dst	84:b2:61:24:a2:00
Src	00:00:00:00:00:00
Seq	0

Probe Request (0x0004)

Dst	84:b2:61:24:a2:00
Src	00:00:00:00:00:00
Seq	0

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	64

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	80

Frame 1 |
2017-01-23T19:31:42.255471Z

Frame 2 |
2017-01-23T19:31:42.264336Z

[Frame 13] Probe Request – active scanning: client solicits responses from APs; directed (specific SSID) or wildcard (broadcast SSID); faster than passive scanning (beacon-only)

Frame 36 |
2017-01-23T19:31:43.025146Z

Frame 37 |
2017-01-23T19:31:43.025442Z

[Frame 40] Probe Request – active scanning: client solicits responses from APs; directed (specific SSID) or wildcard (broadcast SSID); faster than passive scanning (beacon-only)

[Frame 200] Probe Request – active scanning: client solicits responses from APs; directed (specific SSID) or wildcard (broadcast SSID); faster than passive scanning (beacon-only)