

Cisco AP 1

Client F

Null MAC

AP wired B

AP wired A

qos_marking_boeingblk1_platinum_wired.pcapng

Data (0x0020)

Dst	40:98:4e:5c:c0:28
Src	00:23:5d:c9:5a:c7
BSS	84:b2:61:24:a2:00
Seq	0
Len	36

Data (0x0020)

Dst	00:23:5d:c9:5a:c7
Src	40:98:4e:5c:c0:28
BSS	84:b2:61:24:a2:00
Seq	3843
Len	36

Probe Request (0x0004)

Dst	84:b2:61:24:a2:00
Src	00:00:00:00:00:00
Seq	0

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	64

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	80

Frame 1 |
2017-01-23T19:15:59.987584Z

Frame 2 |
2017-01-23T19:15:59.99132Z

[Frame 11] Probe Request – active scanning: client solicits responses from APs; directed (specific SSID) or wildcard (broadcast SSID); faster than passive scanning (beacon-only)

Frame 15 |
2017-01-23T19:16:00.30505Z

Frame 16 |
2017-01-23T19:16:00.305421Z