

qos_marking_lgnexus5x_alloy_wired.pcapng

Data (0x0020)

Dst

64:bc:0c:50:4b:af

Src

00:23:5d:c9:5a:c7

BSS

84:b2:61:24:a2:00

Seq

0

Len

36

Data (0x0020)

Dst

00:23:5d:c9:5a:c7

Src

64:bc:0c:50:4b:af

BSS

84:b2:61:24:a2:00

Seq

2817

Len

36

Data (0x0020)

Dst

84:b2:61:24:a2:00

Src

84:b2:61:24:a2:00

BSS

84:b2:61:24:a2:00

Seq

0

DTLS Application Data (23)

Version

DTLS 1.0 (0xfeff)

Epoch

1

Length

64

DTLS Application Data (23)

Version

DTLS 1.0 (0xfeff)

Epoch

1

Length

80

Probe Request (0x0004)

Dst

84:b2:61:24:a2:00

Src

00:00:00:00:00:00

Seq

0

Frame 1 |
2017-01-22T23:18:29.620045Z

Frame 2 |
2017-01-22T23:18:29.649691Z

Frame 27 |
2017-01-22T23:18:30.337334Z

Frame 28 |
2017-01-22T23:18:30.337524Z

Frame 30 |
2017-01-22T23:18:30.357469Z

[Frame 76] Probe Request – active scanning: client solicits responses from APs; directed (specific SSID) or wildcard (broadcast SSID); faster than passive scanning (beacon-only)