

AP wired B

AP wired A

Cisco AP 1

Client D

Null MAC

qos_marking_lgnexus5x_platinum_wired.pcapng

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	64

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	80

Data (0x0020)

Dst	64:bc:0c:50:4b:af
Src	00:23:5d:c9:5a:c7
BSS	84:b2:61:24:a2:00
Seq	0
Len	36

Data (0x0020)

Dst	00:23:5d:c9:5a:c7
Src	64:bc:0c:50:4b:af
BSS	84:b2:61:24:a2:00
Seq	2560
Len	36

Probe Request (0x0004)

Dst	84:b2:61:24:a2:00
Src	00:00:00:00:00:00
Seq	0

Frame 1 |
2017-01-22T23:46:36.303008Z

Frame 2 |
2017-01-22T23:46:36.303332Z

Frame 3 |
2017-01-22T23:46:36.40996Z

Frame 4 |
2017-01-22T23:46:36.426554Z

💡 [Frame 179] Probe Request – active scanning: client solicits responses from APs; directed (specific SSID) or wildcard (broadcast SSID); faster than passive scanning (beacon-only)